

# **pbuilder User's Manual**

## **Usage and operations**

---

<b>COLLABORATORS</b>
----------------------

	TITLE : pbuilder User's Manual		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY	Junichi Uekawa	2007-5-27	

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>Introducing pbuilder</b>	<b>1</b>
1.1	Aims of pbuilder . . . . .	1
<b>2</b>	<b>Using pbuilder</b>	<b>2</b>
2.1	Creating a base chroot image tar-ball . . . . .	2
2.2	Updating the base.tgz . . . . .	2
2.3	Building a package using the base.tgz . . . . .	2
2.4	Facilitating Debian Developers' typing, pdebuild . . . . .	3
2.5	Configuration Files . . . . .	3
2.6	Building packages as non-root inside the chroot . . . . .	3
2.7	Using pbuilder for back-porting . . . . .	4
2.8	Mass-building packages . . . . .	4
2.9	Auto-backporting scripts . . . . .	5
2.10	Using pbuilder for automated testing of packages . . . . .	5
2.11	Using pbuilder for testing builds with alternate compilers . . . . .	5
<b>3</b>	<b>Using User-mode-linux with pbuilder</b>	<b>6</b>
3.1	Configuring user-mode-linux . . . . .	6
3.2	Configuring rootstrap . . . . .	6
3.3	Configuring pbuilder-uml . . . . .	7
3.4	Considerations for running pbuilder-user-mode-linux . . . . .	7
3.5	Parallel running of pbuilder-user-mode-linux . . . . .	8
3.6	Using pbuilder-user-mode-linux as a wrapper script to start up a virtual machine . . . . .	8
<b>4</b>	<b>Frequently asked questions</b>	<b>9</b>
4.1	pbuilder create fails . . . . .	9
4.2	Directories that cannot be bind-mounted . . . . .	9
4.3	Logging in to pbuilder to investigate build failure . . . . .	9
4.4	Logging in to pbuilder to modify the environment . . . . .	9
4.5	Setting BUILDRESULTUID for sudo sessions . . . . .	10
4.6	Notes on usage of \$TMPDIR . . . . .	10

---

4.7	Creating a shortcut for running <b>pbuilder</b> with a specific distribution . . . . .	10
4.8	Using environmental variables for running <b>pbuilder</b> for specific distribution . . . . .	10
4.9	Using special apt sources lists, and local packages . . . . .	11
4.10	How to get pbuilder to run apt-get update before trying to satisfy build-dependency . . . . .	11
4.11	Different bash prompts inside pbuilder login . . . . .	11
4.12	Creating a chroot reminder . . . . .	12
4.13	Using /var/cache/apt/archives for the package cache . . . . .	12
4.14	pbuilder back ported to stable Debian releases . . . . .	12
4.15	Warning about LOGNAME not being defined . . . . .	12
4.16	Cannot Build-conflict against an essential package . . . . .	12
4.17	Avoiding the "In: Invalid cross-device link" message . . . . .	12
4.18	Using fakechroot . . . . .	13
4.19	Using debconf inside pbuilder sessions . . . . .	13
4.20	nodev mount options hinder pbuilder activity . . . . .	13
4.21	pbuilder is slow . . . . .	13
4.22	Using pdebuild to sponsor package . . . . .	13
4.23	Why is there a source.changes file in ./? . . . . .	13
4.24	amd64 and i386-mode . . . . .	14
4.25	How to use ccache . . . . .	14
4.26	Using tmpfs for buildplace . . . . .	14
4.27	Using svn-buildpackage together with pbuilder . . . . .	14
<b>5</b>	<b>Troubleshooting and development</b>	<b>15</b>
5.1	Reporting bugs . . . . .	15
5.2	Mailing list . . . . .	15
5.3	IRC Channel . . . . .	15
5.4	Information for pbuilder developers . . . . .	15
<b>6</b>	<b>Other uses of pbuilder</b>	<b>17</b>
6.1	Using pbuilder for small experiments . . . . .	17
6.2	Running little programs inside the chroot . . . . .	17
<b>7</b>	<b>Experimental or wish-list features of pbuilder</b>	<b>18</b>
7.1	Using LVM . . . . .	18
7.2	Using cowdancer . . . . .	18
7.2.1	Using cowdancer for sarge . . . . .	18
7.3	Using pbuilder without tar.gz . . . . .	19
7.4	Using pbuilder in a vserver . . . . .	19

---

---

<b>8</b>	<b>Reference materials</b>	<b>20</b>
8.1	Directory structure outside the chroot . . . . .	20
8.2	Directory structure inside the chroot . . . . .	20
<b>9</b>	<b>Minor archaeological details</b>	<b>22</b>
9.1	Documentation history . . . . .	22
9.2	Possibly inaccurate Background History of pbuilder . . . . .	22
9.2.1	The Time Before pbuilder . . . . .	22
9.2.2	Birth of pbuilder . . . . .	22
9.2.3	And the second year of its life . . . . .	23
9.2.4	Fifth year of pbuilder . . . . .	23

---

# List of Tables

5.1	Directory structure of the testsuite . . . . .	16
8.1	Directory Structure outside the chroot . . . . .	20
8.2	Directory Structure inside the chroot . . . . .	21

# Chapter 1

## Introducing pbuilder

### 1.1 Aims of pbuilder

**pbuilder** stands for Personal Builder, and it is an automatic Debian Package Building system for personal development workstation environments. **pbuilder** aims to be an easy-to-setup system for auto-building Debian packages inside a clean-room environment, so that it is possible to verify that a package can be built on most Debian installations. The clean-room environment is achieved through the use of a base chroot image, so that only minimal packages will be installed inside the chroot.

The Debian distribution consists of free software accompanied with source. The source code within Debian's "main" section must build within Debian "main", with only the explicitly specified build-dependencies installed.

The primary aim of **pbuilder** is different from other auto-building systems in Debian in that its aim is not to try to build as many packages as possible. It does not try to guess what a package needs, and in most cases it tries the worst choice of all if there is a choice to be made.

In this way, **pbuilder** tries to ensure that packages tested against **pbuilder** will build properly in most Debian installations, hopefully resulting in a good overall Debian source-buildability.

The goal of making Debian buildable from source is somewhat accomplished, and has seen good progress. In the past age of Debian 3.0, there were many problems when building from source. More recent versions of Debian is much better.

---

## Chapter 2

# Using pbuilder

There are several simple commands for operation. **pbuilder create**, **pbuilder update**, and **pbuilder build** commands are the typical commands used. Let us look at the commands one by one.

### 2.1 Creating a base chroot image tar-ball

**pbuilder create** will create a base chroot image tar-ball (base.tgz). All other commands will operate on the resulting base.tgz. If the Debian release to be created within chroot is not going to be "sid" (which is the default), the distribution code-name needs to be specified with the **--distribution** command-line option.

**debootstrap**<sup>1</sup> is used to create the bare minimum Debian installation, and then build-essential packages are installed on top of the minimum installation using **apt-get** inside the chroot.

For fuller documentation of command-line options, see the pbuilder.8 manual page. Some configuration will be required for `/etc/pbuilderrc` for the mirror site<sup>2</sup> to use, and proxy configuration may be required to allow access through HTTP. See the pbuilder.5 manual page for details.

### 2.2 Updating the base.tgz

**pbuilder update** will update the base.tgz. It will extract the chroot, invoke **apt-get update** and **apt-get dist-upgrade** inside the chroot, and then recreate the base.tgz (the base tar-ball.)

It is possible to switch the distribution which the base.tgz is targeted at at this point. Specify **--distribution sid --override-config** to change the distribution to sid.<sup>3</sup>

For fuller documentation of command-line options, see the pbuilder.8 manual page

### 2.3 Building a package using the base.tgz

To build a package inside the chroot, invoke **pbuilder build whatever.dsc**. **pbuilder** will extract the base.tgz to a temporary working directory, enter the directory with chroot, satisfy the build-dependencies inside chroot, and build the package. The built packages will be moved to a directory specified with the **--buildresult** command-line option.

The **--basetgz** option can be used to specify which base.tgz to use.

---

<sup>1</sup>debootstrap or cdebootstrap can be chosen

<sup>2</sup>The mirror site should preferably be a local mirror or a cache server, so as not to overload the public mirrors with a lot of access. Use of tools such as apt-proxy would be advisable.

<sup>3</sup>Only upgrading is supported. Debian does not generally support downgrading (yet?).



**pbuilder** will extract a fresh base chroot image from base.tgz. (base.tgz is created with **pbuilder create**, and updated with **pbuilder update**). The chroot is populated with build-dependencies by parsing debian/control and invoking **apt-get**.

For fuller documentation of command-line options, see the pbuilder.8 manual page

## 2.4 Facilitating Debian Developers' typing, pdebuild

**pdebuild** is a little wrapper script that does the most frequent of all tasks. A Debian Developer may try to do **debuild**, and build a package, inside a Debian source directory. **pdebuild** will allow similar control, and allow package to be built inside the chroot, to check that the current source tree will build happily inside the chroot.

**pdebuild** calls **dpkg-source** to build the source packages, and then invokes **pbuilder** on the resulting source package. However, unlike **debuild**, the resulting deb files will be found in the **--buildresult** directory.

See the pdebuild.1 manual page for more details.

There is a slightly different mode of operation available in **pdebuild** since version 0.97. **pdebuild** usually runs **debian/rules clean** outside of the chroot; however, it is possible to change the behavior to run it inside the chroot with the **--use-pdebuild-internal**. It will try to bind mount the working directory inside chroot, and run **dpkg-buildpackage** inside. It has the following characteristics, and is not yet the default mode of operation.

- Satisfies build-dependency inside the chroot before creating source package. (which is a good point that default **pdebuild** could not do).
- The working directory is modified from inside the chroot.
- Building with **pdebuild** does not guarantee that it works with **pbuilder**.
- If making the source package fails, the session using the chroot is wasted (chroot creation takes a bit of time, which should be improved with cowdancer).
- Does not work in the same manner as it used to; for example, **--buildresult** does not have any effect.
- The build inside chroot is ran with the current user outside chroot.

## 2.5 Configuration Files

It is possible to specify all settings by command-line options. However, for typing convenience, it is possible to use a configuration file.

`/etc/pbuilderrc` and `${HOME}/.pbuilderrc` are read in when **pbuilder** is invoked. The possible options are documented in the pbuilder.5 manual page.

It is useful to use **--configfile** option to load up a preset configuration file when switching between configuration files for different distributions.

Please note `${HOME}/.pbuilderrc` supersede system settings. For example, if you are upgrading from sarge to etch, you may need to adjust some part of your local setting just like new `/usr/share/pbuilder/pbuilderrc`, e.g., "unset DEBOOTSTRAPOPTS", to cope with the use of cdebootstrap. The same care is needed if you edited old system setting in `/etc/pbuilderrc`.

## 2.6 Building packages as non-root inside the chroot

**pbuilder** requires full root privilege when it is satisfying the build-dependencies, but most packages do not need root privilege to build, or even refused to build when they are built as root. **pbuilder** can create a user which is only used inside **pbuilder** and use that user id when building, and use the **fakeroot** command when root privilege is required.

**BUILDUSERID** configuration option should be set to a value for a user id that does not already exist on the system, so that it is more difficult for packages that are being built with **pbuilder** to affect the environment outside the chroot. When **BUILDUSER-NAME** configuration option is also set, **pbuilder** will use the specified user name and fakeroor for building packages, instead of running as root inside chroot.

Even when using the fakeroorting method, **pbuilder** will run with root privilege when it is required. For example, when installing packages to the chroot, **pbuilder** will run under root privilege.

To be able to invoke **pbuilder** without being root, you need to use user-mode-linux, as explained in Chapter 3.

## 2.7 Using pbuilder for back-porting

**pbuilder** can be used for back-porting software from the latest Debian distribution to the older stable distribution, by using a chroot that contains an image of the older distribution, and building packages inside the chroot. There are several points to consider, and due to the following reasons, automatic back-porting is usually not possible, and manual interaction is required:

- The package from the unstable distribution may depend on packages or versions of packages which are only available in unstable. Thus, it may not be possible to satisfy Build-Depends: on stable (without additional backporting work).
- The stable distribution may have bugs that have been fixed in unstable which need to be worked around.
- The package in the unstable distribution may have problems building even on unstable.

## 2.8 Mass-building packages

**pbuilder** can be automated, because its operations are non-interactive. It is possible to run **pbuilder** through multiple packages non-interactively. Several such scripts are known to exist. Junichi Uekawa has been running such a script since 2001, and has been filing bugs on packages that fail the test of **pbuilder**. There were several problems with auto-building:

- Build-Dependencies need to install non-interactively, but some packages are so broken that they cannot install without interaction (like postgresql).
- When a library package breaks, or gcc/gcj/g++ breaks, or even bison, a large number of build failures are reported. (gcj-3.0 which had no "javac", bison which got more strict, etc.)
- Some people were quite hostile against build failure reports.

Most of the initial bugs have been resolved in the **pbuilder** sweep done around 2002, but these transitional problems which affect a large portion of Debian Archive do arise from time to time. Regression tests have their values.

A script that was used by Junichi Uekawa in the initial run is now included in the **pbuilder** distribution, as **pbuildd.sh**. It is available in `/usr/share/doc/pbuilder/examples/pbuildd/` and its configuration is in `/etc/pbuilder/pbuildd-config.sh`. It should be easy enough to set up for people who are used to **pbuilder**. It has been running for quite a while, and it should be possible to set the application up on your system also. This version of the code is not the most tested, but should function as a starter.

To set up pbuildd, there are some points to be aware of.

- A file `./avoidlist` needs to be available with the list of packages to avoid building.
- It will try building anything, even packages which are not aimed for your architecture.
- Because you are running random build scripts, it is better to use the fakeroor option of **pbuilder**, to avoid running the build under root privilege.
- Because not all builds are guaranteed to finish in a finite time, setting a timeout is probably necessary, or pbuildd may stall with a bad build.
- Some packages require a lot of disk space, around 2GB seems to be sufficient for the largest packages for the time being. If you find otherwise, please inform the maintainer of this documentation.

## 2.9 Auto-backporting scripts

There are some people who use **pbuilder** to automatically back-port a subset of packages to the stable distribution.

I would like some information on how people are doing it, I would appreciate any feedback or information on how you are doing, or any examples.

## 2.10 Using pbuilder for automated testing of packages

**pbuilder** can be used for automated testing of packages. It has the feature of allowing hooks to be placed, and these hooks can try to install packages inside the chroot, or run them, or whatever else that can be done. Some known tests and ideas:

- Automatic install-remove-upgrade-remove-install-purge-upgrade-purge test-suite (distributed as an example, B91dpgk-i), or just check that everything installs somewhat (`execute_installtest.sh`).
- Automatically running lintian (distributed as an example in `/usr/share/doc/pbuilder/examples/B90lintian`).
- Automatic debian-test of the package? The debian-test package has been removed from Debian. A **pbuilder** implementation can be found as `debian/pbuilder-test` directory, implemented through B92test-pkg script.

To use B92test-pkg script, first, add it to your hook directory.<sup>4</sup> The test files are shell scripts placed in `debian/pbuilder-test/NN_name` (where NN is number) following run-parts standard<sup>5</sup> for file names. After a successful build, packages are first tested for installation and removal, and then each test is ran inside the chroot. The current directory is the top directory of the source-code. This means you can expect to be able to use `./debian/` directory from inside your scripts.

Example scripts for use with pbuilder-test can be found in `/usr/share/doc/pbuilder/examples/pbuilder-test`

## 2.11 Using pbuilder for testing builds with alternate compilers

Most packages are compiled with **gcc** or **g++** and using the default compiler version, which was gcc 2.95 for Debian GNU/Linux 3.0 (i386). However, Debian 3.0 was distributed with other compilers, under package names such as **gcc-3.2** for gcc compiler version 3.2. It was therefore possible to try compiling packages against different compiler versions. **pentium-builder** provides an infrastructure for using a different compiler for building packages than the default gcc, by providing a wrapper script called `gcc` which calls the real gcc. To use **pentium-builder** in **pbuilder**, it is possible to set up the following in the configuration:

```
EXTRAPACKAGES="pentium-builder gcc-3.2 g++-3.2"
export DEBIAN_BUILDARCH=athlon
export DEBIAN_BUILDGCCVER=3.2
```

It will instruct **pbuilder** to install the **pentium-builder** package and also the GCC 3.2 compiler packages inside the chroot, and set the environment variables required for **pentium-builder** to function.

<sup>4</sup>It is possible to specify `--hookdir /usr/share/doc/pbuilder/examples` command-line option to include all example hooks as well.

<sup>5</sup>See run-parts(8). For example, no '.' in file names!

## Chapter 3

# Using User-mode-linux with pbuilder

It is possible to use user-mode-linux by invoking **pbuilder-user-mode-linux** instead of **pbuilder**. **pbuilder-user-mode-linux** doesn't require root privileges, and it uses the copy-on-write (COW) disk access method of **User-mode-linux** which typically makes it much faster than the traditional **pbuilder**.

**User-mode-linux** is a somewhat less proven platform than the standard Unix tools which **pbuilder** relies on (**chroot**, **tar**, and **gzip**) but mature enough to support **pbuilder-user-mode-linux** since its version 0.59. And since then, **pbuilder-user-mode-linux** has seen a rapid evolution.

The configuration of **pbuilder-user-mode-linux** goes in three steps:

- Configuration of user-mode-linux
- Configuration of rootstrap
- Configuration of pbuilder-uml

### 3.1 Configuring user-mode-linux

user-mode-linux isn't completely trivial to set up. It would probably be useful to acquaint yourself with it a bit before attempting to use **rootstrap** or **pbuilder-user-mode-linux**. For details, read `/usr/share/doc/uml-utilities/README.Debian` and the **user-mode-linux** documentation. (It's in a separate package, **user-mode-linux-doc**.)

**user-mode-linux** requires the user to be in the **uml-net** group in order to configure the network unless you are using **slirp**.

If you compile your own kernel, you may want to verify that you enable TUN/TAP support, and you might want to consider the SKAS patch.

### 3.2 Configuring rootstrap

**rootstrap** is a wrapper around **debootstrap**. It creates a Debian disk image for use with UML. To configure rootstrap, there are several requirements.

- Install the rootstrap package.
- TUN/TAP only: add the user to the **uml-net** group to allow access to the network

```
adduser dancer uml-net
```

- TUN/TAP only: Check that the kernel supports the TUN/TAP interface, or recompile the kernel if necessary.

- Set up `/etc/rootstrap/rootstrap.conf`. For example, if the current host is 192.168.1.2, changing following entries to something like this seems to work.

```
transport=tuntap
interface=eth0
gateway=192.168.1.1
mirror=http://192.168.1.2:8081/debian
host=192.168.1.198
uml=192.168.1.199
netmask=255.255.255.0
```

Some experimentation with configuration and running **rootstrap ~/`test.uml`** to actually test it would be handy.

Using slirp requires less configuration. The default configuration comes with a working example.

### 3.3 Configuring pbuilder-uml

The following needs to happen:

- Install the **pbuilder-uml** package.
- Set up the configuration file `/etc/pbuilder/pbuilder-uml.conf` in the following manner. It will be different for slirp.

```
MY_ETH0=tuntap,,,192.168.1.198
UML_IP=192.168.1.199
UML_NETMASK=255.255.255.0
UML_NETWORK=192.168.1.0
UML_BROADCAST=255.255.255.255
UML_GATEWAY=192.168.1.1
PBUILDER_UML_IMAGE="/home/dancer/uml-image"
```

Also, it needs to match the rootstrap configuration.

- Make sure **BUILDPLACE** is writable by the user. Change **BUILDPLACE** in the configuration file to a place where the user has access.
- Run **pbuilder-user-mode-linux create --distribution sid** to create the image.
- Try running **pbuilder-user-mode-linux build**.

### 3.4 Considerations for running pbuilder-user-mode-linux

**pbuilder-user-mode-linux** emulates most of **pbuilder**, but there are some differences.

- **pbuilder-user-mode-linux** does not support all options of **pbuilder** properly yet. This is a problem, and will be addressed as specific areas are discovered.
- `/tmp` is handled differently inside **pbuilder-user-mode-linux**. In **pbuilder-user-mode-linux**, `/tmp` is mounted as `tmpfs` inside UML, so accessing files under `/tmp` from outside user-mode-linux does not work. It affects options like **--configfile**, and when trying to build packages placed under `/tmp`.

### 3.5 Parallel running of pbuilder-user-mode-linux

To run **pbuilder-user-mode-linux** in parallel on a system, there are a few things to bear in mind.

- The create and update methods must not be run when a build is in progress, or the COW file will be invalidated.
- If you are not using slirp, user-mode-linux processes which are running in parallel need to have different IP addresses. Just trying to run the **pbuilder-user-mode-linux** several times will result in failure to access the network. But something like the following will work:

```
for IP in 102 103 104 105; do
  xterm -e pbuilder-user-mode-linux build --uml-ip 192.168.0.$IP \
    20030107/whizzytex_1.1.1-1.dsc &
done
```

When using slirp, this problem does not exist.

### 3.6 Using pbuilder-user-mode-linux as a wrapper script to start up a virtual machine

It is possible to use **pbuilder-user-mode-linux** for other uses than just building Debian packages. **pbuilder-user-mode-linux login** will let a user use a shell inside the user-mode-linux **pbuilder** base image, and **pbuilder-user-mode-linux execute** will allow the user to execute a script inside the image.

You can use the script to install ssh and add a new user, so that it is possible to access inside the user-mode-linux through ssh.

Note that it is not possible to use a script from `/tmp` due to the way **pbuilder-user-mode-linux** mounts a tmpfs at `/tmp`.

The following example script may be useful in starting a sshd inside user-mode-linux.

```
#!/bin/bash

apt-get install -y ssh xbase-clients xterm
echo "enter root password"
passwd
cp /etc/ssh/sshd_config{,-}
sed 's/X11Forwarding.*X11Forwarding yes/' /etc/ssh/sshd_config- > /etc/ssh/sshd_config

/etc/init.d/ssh restart
ifconfig
echo "Hit enter to finish"
read
```

## Chapter 4

# Frequently asked questions

Here, known problems and frequently asked questions are documented. This portion was initially available in README.Debian file, but moved here.

### 4.1 pbuilder create fails

It often happens that **pbuilder** cannot create the latest chroot. Try upgrading **pbuilder** and debootstrap. It is currently only possible to create software that handles the past. Future prediction is a feature which may be added later after we have become comfortable with the past.

There are people who occasionally back port debootstrap to stable versions; hunt for them.

When there are errors with the debootstrap phase, the debootstrap script needs to be fixed. **pbuilder** does not provide a way to work around debootstrap.

### 4.2 Directories that cannot be bind-mounted

Because of the way **pbuilder** works, there are several directories which cannot be bind-mounted when running **pbuilder**. The directories include `/tmp`, `/var/cache/pbuilder`, and system directories such as `/etc` and `/usr`. The recommendation is to use directories under the user's home directory for bind-mounts.

### 4.3 Logging in to pbuilder to investigate build failure

It is possible to invoke a shell session after a build failure. Example hook script are provided as `C10shell` and `C11screen` scripts. `C10shell` script will start bash inside chroot, and `C11screen` script will start GNU screen inside the chroot.

### 4.4 Logging in to pbuilder to modify the environment

It is sometimes necessary to modify the chroot environment. **login** will remove the contents of the chroot after logout. It is possible to invoke a shell using hook scripts. **pbuilder update** executes 'E' scripts, and a sample for invoking a shell is provided as `C10shell`.

```
$ mkdir ~/loginhooks
$ cp C10shell ~/loginhooks/E10shell
$ sudo pbuilder update --hookdir ~/loginhooks/E10shell
```

It is also possible to add `--save-after-exec` and/or `--save-after-login` options to the **pbuilder login** session to accomplish the goal. It is possible to add the `--uml-login-nocow` option to **pbuilder-user-mode-linux login** session as well.

## 4.5 Setting BUILDRESULTUID for sudo sessions

It is possible to set

```
BUILDRESULTUID=$SUDO_UID
```

in `pbuilderrc` to set the proper BUILDRESULTUID when using **sudo**.

## 4.6 Notes on usage of \$TMPDIR

If you are setting \$TMPDIR to an unusual value, of other than `/tmp`, you will find that some errors may occur inside the chroot, such as **dpkg-source** failing.

There are two options, you may install a hook to create that directory, or set

```
export TMPDIR=/tmp
```

in `pbuilderrc`. Take your pick.

An example script is provided as `examples/D10tmp` with **pbuilder**.

## 4.7 Creating a shortcut for running pbuilder with a specific distribution

When working with multiple chroots, it would be nice to work with scripts that reduce the amount of typing. An example script `pbuilder-distribution.sh` is provided as an example. Invoking the script as `pbuilder-etch` will invoke **pbuilder** with a `etch` chroot.

## 4.8 Using environmental variables for running pbuilder for specific distribution

This section<sup>1</sup> describes briefly a way to setup and use multiple **pbuilder** setups by creating a `pbuilderrc` configuration in your home path (`$HOME/.pbuilderrc`) and using the variable "DIST" when running **pbuilder** or **pbuild**.

First, setup `$HOME/.pbuilderrc` to look like:

```
if [ -n "${DIST}" ]; then
    BASETGZ="`dirname $BASETGZ`/${DIST}-base.tgz"
    DISTRIBUTION="${DIST}"
    BUILDRESULT="/var/cache/pbuilder/${DIST}/result/"
    APTCACHE="/var/cache/pbuilder/${DIST}/aptcache/"
fi
```

Then, whenever you wish to use **pbuilder** for a particular distro, assign a value to "DIST" that is one of the distros available for Debian or any Debian based distro you happen to be running (i.e. whatever is found under `/usr/lib/debootstrap/scripts`).

Here's some examples on running **pbuilder** or **pbuild**:

```
DIST=gutsy sudo pbuilder create

DIST=sid sudo pbuilder create --mirror http://http.us.debian.org/debian

DIST=gutsy sudo pbuilder create \
    --othermirror "deb http://archive.ubuntu.com/ubuntu gutsy universe \
```

---

<sup>1</sup>This part of the documentation contributed by Andres Mejia  
This example was taken from a wiki (<https://wiki.ubuntu.com/PbuilderHowto>).



```

    multiverse"

DIST=gutsy sudo pbuilder update

DIST=sid sudo pbuilder update --override-config --mirror \
http://http.us.debian.org/debian \
--othermirror "deb http://http.us.debian.org/debian sid contrib non-free"

DIST=gutsy pdebuild

```

## 4.9 Using special apt sources lists, and local packages

If you have some very specialized requirements on your apt setup inside **pbuilder**, it is possible to specify that through the **--othermirror** option. Try something like: **--othermirror "deb http://local/mirror stable main|deb-src http://local/source/repository ./"**

To use the local file system instead of HTTP, it is necessary to do bind-mounting. **--bindmounts** is a command-line option useful for such cases.

It might be convenient to use your built packages from inside the chroot. It is possible to automate the task with the following configuration. First, set up **pbuilder** to bindmount your build results directory.

```
BINDMOUNTS="/var/cache/pbuilder/result"
```

Then, add the following hook

```

# cat /var/cache/pbuilder/hooks/D70results
#!/bin/sh
cd /var/cache/pbuilder/result/
/usr/bin/dpkg-scanpackages . /dev/null > /var/cache/pbuilder/result/Packages
/usr/bin/apt-get update

```

This way, you can use **debfile:/var/cache/pbuilder/result**

## 4.10 How to get pbuilder to run apt-get update before trying to satisfy build-dependency

You can use hook scripts for this. D scripts are run before satisfying build-dependency.

This snippet comes from Ondrej Sury.

## 4.11 Different bash prompts inside pbuilder login

To make distinguishing bash prompts inside **pbuilder** easier, it is possible to set environment variables such as **PS1** inside **pbuilder**.

With versions of bash more recent than 2.05b-2-15, the value of the **debian\_chroot** variable, if set, is included in the value of **PS1** (the Bash prompt) inside the chroot. In prior versions of bash,<sup>2</sup> setting **PS1** in **pbuilder** worked.

example of **debian\_chroot**

```
export debian_chroot="pbuidl$$"
```

example of **PS1**

```
export PS1="pbuidl chroot 32165 # "
```

<sup>2</sup>Versions of bash from and before Debian 3.0

## 4.12 Creating a chroot reminder

Bash prompts will help you remember that you are inside a chroot. There are other cases where you may want other signs of being inside a chroot. Check out the `examples/F90chrootmemo` hook script. It will create a file called `/CHROOT` inside your chroot.

## 4.13 Using `/var/cache/apt/archives` for the package cache

For the help of low-bandwidth systems, it is possible to use `/var/cache/apt/archives` as the package cache. Just specify it instead of the default `/var/cache/pbuilder/aptcache`.

It is however not possible to do so currently with the user-mode-linux version of **pbuilder**, because `/var/cache/apt/archives` is usually only writable by root.

Use of dedicated tools such as `apt-proxy` is recommended, since caching of packages would benefit the system outside the scope of **pbuilder**.

## 4.14 pbuilder back ported to stable Debian releases

Currently stable back port of pbuilder is available at [backports.org](http://backports.org).

## 4.15 Warning about LOGNAME not being defined

You might see a lot of warning messages when running **pbuilder**.

```
dpkg-genchanges: warning: no utmp entry available and LOGNAME not defined; using uid of ↵  
process (1234)
```

It is currently safe to ignore this warning message. Please report back if you find any problem with having `LOGNAME` unset. Setting `LOGNAME` caused a few problems when invoking **chroot**. For example, `dpkg` requires `getpwnam` to succeed inside chroot, which means `LOGNAME` and the related user information have to be set up inside chroot.

## 4.16 Cannot Build-conflict against an essential package

**pbuilder** does not currently allow Build-Conflicts against essential packages. It should be obvious that essential packages should not be removed from a working Debian system, and a source package should not try to force removal of such packages on people building the package.

## 4.17 Avoiding the "ln: Invalid cross-device link" message

By default, **pbuilder** uses hard links to manage the **pbuilder** package cache. It is not possible to make hard links across different devices; and thus this error will occur, depending on your set up. If this happens, set

```
APTCACHEHARDLINK=no
```

in your `pbuilder.rc` file. Note that packages in **APTCACHE** will be copied into chroot local cache, so plan for enough space on **BUILDPLACE** device.

## 4.18 Using fakechroot

It is possible to use **fakechroot** instead of being root to run **pbuilder**; however, several things make this impractical. **fakechroot** overrides library loads and tries to override default libc functions when providing the functionality of virtual **chroot**. However, some binaries do not use libc to function, or override the overriding provided by **fakechroot**. One example is **ldd**. Inside **fakechroot**, **ldd** will check the library dependency outside of the chroot, which is not the expected behavior.

To work around the problem, **debootstrap** has a `--variant fakechroot` option. Use that, so that **ldd** and **ldconfig** are overridden.

Make sure you have set your `LD_PRELOAD` path correctly, as described in the **fakechroot** manpage.

## 4.19 Using debconf inside pbuilder sessions

To use **debconf** inside **pbuilder**, setting `DEBIAN_FRONTEND` to 'readline' in `pbuildererrc` should work. Setting it to 'dialog' should also work, but make sure **whiptail** or **dialog** is installed inside the chroot.

## 4.20 nodev mount options hinder pbuilder activity

If you see messages such as this when building a chroot, you are mounting the file system with the `nodev` option.

```
/var/lib/dpkg/info/base-files.postinst: /dev/null: Permission denied
```

You will also have problems if you mount the file system with the `noexec` option, or `nosuid`. Make sure you do not have these flags set when mounting the file system for `/var/cache/pbuilder` or `$BUILDPLACE`.

This is not a problem when using **user-mode-linux**.

See [316135](#) for example.

## 4.21 pbuilder is slow

**pbuilder** is often slow. The slowest part of **pbuilder** is extracting the `tar.gz` every time **pbuilder** is invoked. That can be avoided by using **pbuilder-user-mode-linux**. **pbuilder-user-mode-linux** uses COW file system, and thus does not need to clean up and recreate the root file system.

**pbuilder-user-mode-linux** is slower in executing the actual build system, due to the usual **user-mode-linux** overhead for system calls. It is more friendly to the hard drive.

**pbuilder** with **cowdancer** is also an alternative that improves speed of **pbuilder** startup.

## 4.22 Using pdebuild to sponsor package

To sign a package marking for sponsorship, it is possible to use `--auto-debsign` and `--debsign-k` options of **pdebuild**.

```
pdebuild --auto-debsign --debsign-k XXXXXXXX
```

## 4.23 Why is there a source.changes file in ../?

When running **pdebuild**, **pbuilder** will run `dpkg-buildpackage` to create a Debian source package to pass it on to **pbuilder**. File named `XXXX_YYY_source.changes` is what remains from that process. It is harmless unless you try to upload it to the Debian archive.

This behavior is different when running through `--use-pdebuild-internal`

## 4.24 amd64 and i386-mode

amd64 architectures are capable of running binaries in i386 mode. It is possible to use **pbuilder** to run packages, using **linux32** and **debootstrap --arch** option. Specifically, a command-line option like the following will work.

```
pbuilder create --distribution sid --debootstrapopts --arch --debootstrapopts i386 \  
  --basetgz /var/cache/pbuilder/base-i386.tgz --mirror http://ftp.jp.debian.org/debian  
linux32 pbuilder build --basetgz /var/cache/pbuilder/base-i386.tgz
```

## 4.25 How to use ccache

To use **ccache** with **pbuilder**, use the following configuration. Note that the directory used for **CCACHE\_DIR** needs to exist, and be writable by user within **chroot**. The default user within **chroot** is

```
uid=1234
```

.

Example is provided as **pbuilderccache**.

```
export CCACHE_DIR="/var/cache/pbuilder/ccache"  
export PATH="/usr/lib/ccache:${PATH}"
```

```
EXTRAPACKAGES=ccache  
BINDMOUNTS="${CCACHE_DIR}"
```

[This entry created thanks to a blog posting.](#)

## 4.26 Using tmpfs for buildplace

To improve speed of operation, it is possible to use tmpfs for pbuilder build location. Mount tmpfs to **/var/cache/pbuilder/build**, and set

```
APT_CACHE_HARDLINK=no
```

.

## 4.27 Using svn-buildpackage together with pbuilder

**pdebuild** command can be used with **svn-buildpackage --svn-builder** command-line option. <sup>3</sup>

```
alias svn-cowbuilder="svn-buildpackage --svn-builder='pdebuild --pbuilder cowbuilder'"
```

---

<sup>3</sup>[Zack has posted an example on his blog.](#)

## Chapter 5

# Troubleshooting and development

### 5.1 Reporting bugs

To report bugs, it would be important to have a log of what's going wrong. Most of the time, adding a `--debug` option and re-running the session should do the trick. Please send the log of such session along with your problem to ease the debugging process.

### 5.2 Mailing list

There is a mailing list for **pbuilder** on alioth ([pbuilder-maint@lists.alioth.debian.org](mailto:pbuilder-maint@lists.alioth.debian.org)). You can subscribe through the alioth web interface. [http://alioth.debian.org/mail/?group\\_id=30778](http://alioth.debian.org/mail/?group_id=30778).

### 5.3 IRC Channel

For coordination and communication, IRC channel `#pbuilder` on `irc.oftc.net` is used. Please log your intent there when you are going to start doing some changes and committing some change.

### 5.4 Information for pbuilder developers

This section tries to document current development practices and how things generally operate in development.

**pbuilder** is co-maintained with resources provided by Alioth. There is an Alioth project page at <http://alioth.debian.org/projects/-pbuilder>. Home page is also available, at <http://alioth.debian.org/projects/pbuilder> which shows this text. git repository is available through http, git, or (if you have an account on alioth, ) ssh.

```
git-clone git://git.debian.org/git/pbuilder/pbuilder.git
git-clone http://git.debian.org/git/pbuilder/pbuilder.git
git-clone ssh://git.debian.org/git/pbuilder/pbuilder.git
```

Test-suites are available in `./testsuite/` directory. Changes are expected not to break the test-suites. `./run-test.sh` is a basic test-suite, which puts a summary in `run-test.log`, and `run-test-cdebootstrap.log`. `./run-test-regression.sh` is a regression test-suite, which puts the result in `run-test-regression.log`. Currently, `run-test.sh` is ran automatically daily to ensure that pbuilder is working.

When making changes, changes should be documented in the Git commit log. `git-dch` will generate `debian/changelog` from the commit log. Make the first line of your commit log meaningful, and add any bug-closing information available.

Directory	Meaning
<code>./testsuite/</code>	Directory for testsuite
<code>./testsuite/run-test.sh</code>	Daily regression test to test against Debian Archive changes breaking pbuilder.
<code>./testsuite/run-test.log</code>	A summary of testsuite
<code>./testsuite/normal/</code>	Directory for testsuite results of running pbuilder with debootstrap
<code>./testsuite/cdebootstrap/</code>	Directory for testsuite results of running pbuilder with cdebootstrap
<code>./testsuite/run-regression.sh</code>	Regression testsuite, ran every time change is made to pbuilder to make sure there is no regression.
<code>./testsuite/run-regression.log</code>	Summary of test result
<code>./testsuite/regression/BugID-*.sh</code>	Regression tests, exit 0 for success, exit 1 for failure
<code>./testsuite/regression/BugID-*</code>	Files used for the regression testsuite.
<code>./testsuite/regression/log/BugID-*.sh.log</code>	Output of the regression test, output from the script is redirected by run-regression.sh

Table 5.1: Directory structure of the testsuite

A TODO file is available in `debian/TODO`. It's mostly not well-maintained, but hopefully it will be more up-to-date when people start using it. `emacs todoo-mode` is used in editing the file.

When releasing a new version of **pbuilder**, the version is tagged with the git tag `X.XXX` (version number). This is done with `./git-tag.sh` script available in the source tree.

## Chapter 6

# Other uses of pbuilder

### 6.1 Using pbuilder for small experiments

There are cases when some small experimenting is required, and you do not want to damage the main system, like when installing experimental library packages, or compiling with experimental compilers. For such cases, the **pbuilder login** command is available.

**pbuilder login** is a debugging feature for **pbuilder** itself, but it also allows users to have a temporary chroot.

Note that the chroot is cleaned after logging out of the shell, and mounting file systems inside it is considered harmful.

### 6.2 Running little programs inside the chroot

To facilitate using **pbuilder** for other uses, **pbuilder execute** is available. **pbuilder execute** will take a script specified in the command-line argument, and invoke the script inside the chroot.

The script can be useful for sequences of operations such as installing ssh and adding a new user inside the chroot.

---

## Chapter 7

# Experimental or wish-list features of pbuilder

There are some advanced features, above that of the basic feature of **pbuilder**, for some specific purposes.

### 7.1 Using LVM

LVM2 has a useful snapshot function that features Copy-on-write images. That could be used for **pbuilder** just as it can be used for the user-mode-linux **pbuilder** port. `lvmpbuilder` script in the examples directory implements such port. The scripts and documentation can be found under `/usr/share/doc/pbuilder/examples/lvmpbuilder/`

### 7.2 Using cowdancer

**cowdancer** allows copy-on-write semantics on file system using hard links and hard-link-breaking-on-write tricks. **pbuilder** using **cowdancer** seems to be much faster and it is one ideal point for improvement. **cowbuilder**, a wrapper for **pbuilder** for using **cowdancer** is available from **cowdancer** package since 0.14

Example command-lines for `cowbuilder` look like the following.

```
# cowbuilder --create --distribution sid
# cowbuilder --update --distribution sid
# cowbuilder --build XXX.dsc
```

It is also possible to use `cowdancer` with `pdebuild` command. Specify with command-line option `--pbuilder` or set it in `PDEBUILD_PBUILDER` configuration option.

```
$ pdebuild --pbuilder cowbuilder
```

#### 7.2.1 Using cowdancer for sarge

This section is mostly obsolete now that `etch` is released, but left for reference, and will be removed after `lenny` release.

`cowdancer` was introduced after the release of Debian `sarge`; if you want to build packages for `sarge` with `cowbuilder`, you will need to workaround its unavailability.

One way to workaround the problem is to set `APTCONFDIR` in `pbuilder.rc` to point to a directory with a list of sources for APT which has both `sarge` and `sarge-backports`.

```
$ cat sources.list
# sarge-backports
deb      http://www.backports.org/debian sarge-backports main
deb-src  http://www.backports.org/debian sarge-backports main
```



```
# sarge
deb      http://ftp.de.debian.org/debian sarge main
deb-src  http://ftp.de.debian.org/debian sarge main
```

It is recommended to "Pin" the cowdancer package appropriately in this case, via the APT preferences mechanism.

```
$ cat preferences
Explanation: use cowdancer from backports
Package: cowdancer
Pin: release a=sarge-backports
Pin-Priority: 950
```

## 7.3 Using pbuilder without tar.gz

The **--no-targz** option of **pbuilder** will allow usage of **pbuilder** in a different way from conventional usage. It will try to use an existing chroot, and will not try to clean up after working on it. It is an operation mode more like **sbuid**.

It should be possible to create base chroot images for **dchroot** with the following commands:

```
# pbuilder create --distribution etch --no-targz --basetgz /chroot/etch
# pbuilder create --distribution lenny --no-targz --basetgz /chroot/lenny
# pbuilder create --distribution sid --no-targz --basetgz /chroot/sid
```

## 7.4 Using pbuilder in a vserver

It is possible to use **pbuilder** in a vserver environment. This requires either vserver-patches in version 2.1.1-rc14 or higher, or a Linux kernel version 2.6.16 or higher.

To use **pbuilder** in a vserver, you need to set the **secure\_mount CAPS** in the **ccapabilities** of this vserver.

## Chapter 8

# Reference materials

### 8.1 Directory structure outside the chroot

Directory	Meaning
/etc/pbuilderrc	configuration file
/usr/share/pbuilder/pbuilderrc	Default configuration
/var/cache/pbuilder/base.tgz	Default location pbuilder uses for base.tgz, the tar-ball containing a basic Debian installation with only the build-essential packages.
/var/cache/pbuilder/build/PID/	Default location pbuilder uses for chroot
/var/cache/pbuilder/aptcache	Default location <b>pbuilder</b> will use as apt cache, to store deb packages required during <b>pbuilder</b> build.
/var/cache/pbuilder/result	Default location <b>pbuilder</b> puts the deb files and other files created after build
/var/cache/pbuilder/pbuilder-umlresult	Default location <b>pbuilder-user-mode-linux</b> puts the deb files and other files created after build
/var/cache/pbuilder/pbuilder-mnt	Default location <b>pbuilder-user-mode-linux</b> uses for mounting the COW file system, for chrooting.
/tmp	<b>pbuilder-user-mode-linux</b> will mount tmpfs for work.
\${HOME}/tmp/PID.cow	<b>pbuilder-user-mode-linux</b> use this directory for location of COW file system.
\${HOME}/uml-image	<b>pbuilder-user-mode-linux</b> use this directory for user-mode-linux full disk image.

Table 8.1: Directory Structure outside the chroot

### 8.2 Directory structure inside the chroot

Directory	Meaning
/etc/mtab	symlink to /proc/mounts.
/tmp/builddd	Default place used in <b>pbuilder</b> to place the Debian package to be processed. /tmp/builddd/package-name-version/ will be the root directory of the package being processed. HOME environment variable is set to this value inside chroot by pbuilder-buildpackage
/run	The script passed as an argument to <b>pbuilder</b> execute is passed on.
/tmp/hooks	The location of hooks.
/var/cache/apt/archives	<b>pbuilder</b> copies the content of this directory to and from the aptcache directory of outside chroot.
/tmp/XXXX	<b>pbuilder-user-mode-linux</b> uses a script in /tmp to bootstrap into user-mode-linux

Table 8.2: Directory Structure inside the chroot

## Chapter 9

# Minor archaeological details

### 9.1 Documentation history

This document was started on 28 Dec 2002 by Junichi Uekawa, trying to document what is known about **pbuilder**.

This documentation is available from the **pbuilder** source tar-ball, and from the git repository of **pbuilder** (web-based access is possible). A copy of this documentation can be found on the [Alioth project page for pbuilder](http://pbuilder.alioth.debian.org/). There is also a [PDF version](#). The homepage for **pbuilder** is <http://pbuilder.alioth.debian.org/> hosted by alioth project.

Documentation is written using DocBook XML, with emacs PSGML mode, and using wysidocbookxml for live previewing.

### 9.2 Possibly inaccurate Background History of pbuilder

The following is a most possibly inaccurate account of how **pbuilder** came to happen, and other attempts to make something like **pbuilder** happen. This part of the document was originally in the AUTHORS file, to give credit to those who existed before **pbuilder**.

#### 9.2.1 The Time Before pbuilder

There was once dbuild, which was a shell script to build Debian packages from source. Lars Wirzenius wrote that script, and it was good, short, and simple (probably). There was nothing like build-depends then (I think), and it was simple. It could have been improved, I could only find references and no actual source.

debbuild was probably written by James Troup. I don't know it because I have never seen the actual code, I could only find some references to it on the net, and mailing list logs.

sbuild is a perl script to build Debian packages from source. It parses Build-Depends, and performs other miscellaneous checks, and has a lot of hacks to actually get things building, including a table of what package to use when virtual packages are specified (does it do that still?). It supports the use of a local database for packages which do not have build-dependencies. It was written by Ronan Hodek, and I think it was patched and fixed and extended by several people. It is part of wanna-build, and used extensively in the Debian build system. I think it was maintained mostly by Ryan Murray.

#### 9.2.2 Birth of pbuilder

wanna-build (sbuild) was (at the time of year 2001) quite difficult to set up, and it was never a Debian package. dbuild was something that predated Build-Depends.

Building packages from source using Build-Depends information within a chroot sounded trivial; and **pbuilder** was born. It was initially a shell script with only a few lines, which called debootstrap and chroot and dpkg-buildpackage in the same run, but soon, it was decided that that's too slow.

---

Yes, and it took almost an year to get things somewhat right, and in the middle of the process, Debian 3.0 was released. Yay. Debian 3.0 wasn't completely buildable with **pbuilder**, but the amount of packages which are not buildable is steadily decreasing (I hope).

### 9.2.3 And the second year of its life

Someone wanted **pbuilder** to not run as root, and as User-mode-linux has become more useful as time passed, I've started experimenting with **pbuilder-user-mode-linux**. **pbuilder-user-mode-linux** has not stayed functional as much as I would have liked, and bootstrapping **user-mode-linux** environment has been pretty hard, due to the quality of user-mode-linux code or packaging at that time, which kept on breaking network support in one way or the other.

### 9.2.4 Fifth year of pbuilder

**pbuilder** is now widely adopted as a 'almost standard' tool for testing packages, and building packages in a pristine environment. There are other similar tools that do similar tasks, but they do not share the exact same goal. To commemorate this fact, **pbuilder** is now co-maintained with several people.

**sbuild** is now a well-maintained Debian package within Debian, and with **pbuilder** being such a slow monster, some people prefer the approach of sbuild. Development to use LVM-snapshots, cowloop, or cowdancer is hoped to improve the situation somewhat.

---